



HUAWEI TECHNIAL TEXTILE

Technical Sheet

Green House
Transparent

Product Code

| | | | | |
|---------------------------------------|--|--------------------------|------------------------|------------------------|
| Total Weight | DIN EN ISO 2286-2 ASTM D-751.10 | 400g/m2 11.8oz/sq. yd | 440g/m2 13oz/sq. yd | 510g/m2 15oz/sq. yd |
| Yarn | Denier | 1000x1000D | 1000x1000D | 1000x1000D |
| Yarn Count | Per Inch | 3x3 | 3x3 | 3x3 |
| Tensile Strength Warp/Weft | DIN EN ISO 1421/V1 ASTM D-751 B | 1100/1000 N/50mm | 1100/1000 N/50mm | 1100/1000 N/50mm |
| Tear Strength Warp/Weft | DIN 53363 ASTM D-751 (8 “ x 10 “) Specimen | 100/90 N | 100/90 N | 100/90 N |
| Adhesion | ASTM D-751 RF Weld | 80N/50mm | 80N/50mm | 80N/50mm |
| Temperature resistance | DIN EN 1876-1 ASTM D-2136 | (-40° C/+70° C | (-40° C/+70° C | (-40° C/+70° C |
| Fire behaviour | ISO 3795 | B2 | B2 | B2 |
| Environmental Protective | EU | REACH | REACH | REACH |
| Surface Treatment | Acrylic/PVDF | NA | NA | NA |
| Weather Protection | | UV | UV | UV |
| Special Property | | NA | NA | NA |
| Available Width | Meter | 1-3.2m | 1-3.2m | 1-3.2m |

Leading China PVC Fabric Producer

www.chinatarps.com Manager@chinatarps.com 0086-13757342702