



HUAWEI TECHNIAL TEXTILE

Technical Sheet

WaterTank Fabric /
Tank Liner

Product Code

Total Weight	DIN EN ISO 2286-2	680g/m ²	900g/m ²
	ASTM D-751.10	20oz/sq. yd	26.5oz/sq. yd
Yarn	Denier	1000x1000D	1000x1000D
Yarn Count	Per Inch	23x23	12x12 panama
Tensile Strength Warp/Weft	DIN EN ISO 1421/V1	3000/2900	3800/3500
	ASTM D-751 B	N/50mm	N/50mm
Tear Strength Warp/Weft	DIN 53363	330/310	430/400
	ASTM D-751 (8 “ x 10 “) Specimen	N	N
Adhesion	ASTM D-751 RF Weld	100N/50mm	100N/50mm
Temperature resistance	DIN EN 1876-1	(-40° C/+70° C. (-40° C/+70° C.	
	ASTM D-2136		
Fire behaviour	ISO 3795	B2	B2
Environmental Protective	EU	REACH	REACH
Surface Treatment	Acrylic/PVDF	NA	NA
Weather Protection		UV	UV
Special Property			
Available Width	Meter	1-3.2m	1-3.2m

Leading China PVC Fabric Producer

www.chinatarps.com Manager@chinatarps.com 0086-13757342702