



# HUAWEI TECHNIAL TEXTILE

## Technical Sheet

Door Seal/ Dock Shelter

Product Code

<b>Total Weight</b>	DIN EN ISO 2286-2 ASTM D-751.10	610g/m2 18oz/sq. yd	3800g/m2 112oz/sq. yd	3800g/m2 112oz/sq. yd
<b>Yarn</b>	Denier	1000x1000D	2 Layer	2 layer
<b>Yarn Count</b>	Per Inch	20x20	2 Layer	2 Layer
<b>Tensile Strength Warp/Weft</b>	DIN EN ISO 1421/V1 ASTM D-751 B	2500/2400 N/50mm	10000/10000 N/50mm	9500/9500 N/50mm
<b>Tear Strength Warp/Weft</b>	DIN 53363 ASTM D-751 (8 “ x 10 “) Specimen	280/270 N	5000/5000 N	3000/3000 N
<b>Adhesion</b>	ASTM D-751 RF Weld	95N/50mm	120N/50mm	120N/50mm
<b>Temperature resistance</b>	DIN EN 1876-1 ASTM D-2136	(-40° C/+70° C.	(-40° C/+70° C.	(-40° C/+70° C.
<b>Fire behaviour</b>	ISO 3795	B2	B2	B2
<b>Environmental Protective</b>	EU	REACH	REACH	REACH
<b>Surface Treatment</b>	Acrylic/PVDF	NA	NA	NA
<b>Weather Protection</b>		Anti UV/Mildew	Anti UV/Mildew	Anti UV/Mildew
<b>Special Property</b>				
<b>Available Width</b>	Meter	1-3.2m	0.5-2m	0.5-2m

Leading China PVC Fabric Producer

www.chinatarps.com Manager@chinatarps.com 0086-13757342702