



HUAWEI TECHNIAL TEXTILE

Technical Sheet

Fire Blanket

Product Code

Total Weight	DIN EN ISO 2286-2	510g/m2	610g/m2	700g/m2
	ASTM D-751.10	15oz/sq. yd	18oz/sq. yd	20.5oz/sq. yd
Yarn	Denier	1000x1000D	1000x1000D	1000x1000D
Yarn Count	Per Inch	20x20	20x20	20x22
Tensile Strength Warp/Weft	DIN EN ISO 1421/V1	2500/2400	2600/2500	2700/2600
	ASTM D-751 B	N/50mm	N/50mm	N/50mm
Tear Strength Warp/Weft	DIN 53363	270/260	280/270	290/290
	ASTM D-751 (8 “ x 10 “) Specimen	N	N	N
Adhesion	ASTM D-751 RF Weld	90N/50mm	90N/50mm	90N/50mm
Temperature resistance	DIN EN 1876-1	-40° C/+70° C	-40° C/+70° C	-40° C/+70° C
	ASTM D-2136			
Fire behaviour	ISO 3795	B2	B2	B2
Environmental Protective	EU	Food Grade	Food Grade	Food Grade
	Acrylic/PVDF	NA	NA	NA
Weather Protection		UV	UV	UV
Special Property				
Available Width	Meter	1-3.2m	1-3.2m	1-3.2m

Leading China PVC Fabric Producer

www.chinatarps.com Manager@chinatarps.com 0086-13757342702