



HUAWEI TECHNIAL TEXTILE

Technical Sheet

Ventilation/ Flexible Ducting	Product Code							
Total Weight	DIN EN ISO 2286-2 ASTM D-751.10	440g/m2 13oz/sq. yd	550g/m2 16oz/sq. yd	610g/m2 18oz/sq. yd	650g/m2 19oz/sq. yd	700g/m2 20.5oz/sq. yd	750g/m2 20.5oz/sq. yd	
Yarn	Denier	1000x1000D	1000x1000D	2000x2000	1300x1300D	1300x1300D	1000x2000D	
Yarn Count	Per Inch	9x9	12x12	9x9	12x12	12x12	20x22	
Tensile Strength Warp/Weft	DIN EN ISO 1421/V1 ASTM D-751 B	1500/1500 N/50mm	2000/1900 N/50mm	2200/2100 N/50mm	2500/2300 N/50mm	2500/2300 N/50mm	2700/2500 N/50mm	
Tear Strength Warp/Weft	DIN 53363 ASTM D-751 (8 " x 10 ") Specimen	180/160 N	250/230 N	320/280 N	350/330 N	360/340 N	320/320 N	
Adhesion	ASTM D-751 RF Weld	90N/50mm	90N/50mm	90N/50mm	90N/50mm	90N/50mm	90N/50mm	
Temperature resistance	DIN EN 1876-1 ASTM D-2136	-40° C/+70° C	-40° C/+70° C	-40° C/+70° C	-40° C/+70° C	-40° C/+70° C	-40° C/+70° C	-40° C/+70° C
Fire behaviour	ISO 3795	B2	B2	B2	B2	B2	B2	
Environmental Protective	EU							
Surface Treatment	Acrylic/PVDF	NA	NA	NA	NA	NA	NA	
Weather Protection		NA	NA	NA	NA	NA	NA	
Special Property		Antistatic	Antistatic	Antistatic	Antistatic	Antistatic	Antistatic	
Available Width	Meter	1-3.2m	1-3.2m	1-3.2m	1-3.2m	1-3.2m	1-3.2m	

Leading China PVC Fabric Producer

www.chinatarps.com Manager@chinatarps.com 0086-13757342702