



HUAWEI TECHNIAL TEXTILE

Technical Sheet

Swimming Pool Fabric	Product Code				
Total Weight	DIN EN ISO 2286-2	580g/m ²	610g/m ²	750g/m ²	1000g/m ²
	ASTM D-751.10	17oz/sq. yd	18oz/sq. yd	22oz/sq. yd	30oz/sq. yd
Yarn	Denier	1000x1000D	1000x1000D	1000x1000D	1000x1000D
Yarn Count	Per Inch	20x20	20x20	23x23	28x26
Tensile Strength Warp/Weft	DIN EN ISO 1421/V1	2600/2500	2700/2600	3000/2900	3500/3200
	ASTM D-751 B	N/50mm	N/50mm	N/50mm	N/50mm
Tear Strength Warp/Weft	DIN 53363	260/250	280/270	320/300	360/350
	ASTM D-751 (8 " x 10 ") Specimen	N	N	N	N
Adhesion	ASTM D-751 RF Weld	95N/50mm	95N/50mm	95N/50mm	95N/50mm
Temperature resistance	DIN EN 1876-1	-40° C/+70° C	-40° C/+70° C	-40° C/+70° C	-40° C/+70° C
	ASTM D-2136				
Fire behaviour	ISO 3795	B2	B2	B2	B2
Environmental Protective	EU	Food Grade	Food Grade	Food Grade	Food Grade
Surface Treatment	Acrylic/PVDF	NA	NA	NA	NA
Weather Protection		UV	UV	UV	UV
Special Property					
Available Width	Meter	1-3.2m	1-3.2m	1-3.2m	1-3.2m

Leading China PVC Fabric Producer

www.chinatarps.com Manager@chinatarps.com 0086-13757342702