



# HUAWEI TECHNIAL TEXTILE

## Technical Sheet

Pergola	Product Code	3D Emboss		
Total Weight	DIN EN ISO 2286-2	545g/m <sup>2</sup>	750g/m <sup>2</sup>	850g/m <sup>2</sup>
	ASTM D-751.10	16oz/sq. yd	22oz/sq. yd	25oz/sq. yd
Yarn	Denier	1000x1000D	1000x1000D	1000x1000D
Yarn Count	Per Inch	9x9	23x23	23x23
Tensile Strength Warp/Weft	DIN EN ISO 1421/V1	1600/1500	2900/2800	3000/2900
	ASTM D-751 B	N/50mm	N/50mm	N/50mm
Tear Strength Warp/Weft	DIN 53363	180/160	300/290	310/300
	ASTM D-751 (8 “ x 10 “) Specimen	90N	100N	100N
Adhesion	ASTM D-751 RF Weld	N/50mm	N/50mm	N/50mm
Temperature resistance	DIN EN 1876-1	-40° C/+70° C	-40° C/+70° C	-40° C/+70° C
	ASTM D-2136			
Fire behaviour	ISO 3795			
Environmental Protective	EU			
Surface Treatment	Acrylic/PVDF	NA	Acrylic	Acrylic
Weather Protection		Anti UV/Mildew	Anti UV/Mildew	Anti UV/Mildew
	Special Property	Blockout	Blockout	Blockout
Available Width	Meter	1-5m	1-3.2m	1-3.2m

Leading China PVC Fabric Producer

www.chinatarps.com Manager@chinatarps.com 0086-13757342702