



HUAWEI TECHNIAL TEXTILE

Technical Sheet

Membrane Structure	Product Code	Type1	Type2	Type3	Type4
Total Weight	DIN EN ISO 2286-2	720g/m2	950g/m2	1200g/m2	1400g/m2
	ASTM D-751. 10	21oz/sq. yd	28oz/sq. yd	35oz/sq. yd	41oz/sq. yd
Yarn	Denier	1000x1000D	1000x1000D	1100x1100D	1500x1500D
Yarn Count	Per Inch	23x23	12x12panama	12x12panama	12x12panama
Tensile Strength Warp/Weft	DIN EN ISO 1421/V1	3200/3000	4200/4000	5200/5000	6200/6000
	ASTM D-751 B	N/50mm	N/50mm	N/50mm	N/50mm
Tear Strength Warp/Weft	DIN 53363	330/320	450/430	500/480	650/600
	ASTM D-751 (8 “ x 10 “) Specimen	N	N	N	N
Adhesion	ASTM D-751 RF Weld	N/50mm	N/50mm	N/50mm	N/50mm
Temperature resistance	DIN EN 1876-1	-40° C/+70° C	-40° C/+70° C	-40° C/+70° C	-40° C/+70° C
	ASTM D-2136				
Fire behaviour	ISO 3795	B1	B1	B1	B1
Environmental Protective	EU	REACH	REACH	REACH	REACH
Surface Treatment	Acrylic/PVDF	Acrylic	Acrylic	PVDF	PVDF
Weather Protection		Anti UV/Mildew	Anti UV/Mildew	Anti UV/Mildew	Anti UV/Mildew
Special Property		Weldable	Weldable	Weldable	Weldable
Available Width	Meter	3m	3m	3m	3m

Leading China PVC Fabric Producer

www.chinatarps.com Manager@chinatarps.com 0086-13757342702