



HUAWEI TECHNIAL TEXTILE

Technical Sheet

Transparent PVC Product Code

Total Weight	DIN EN ISO 2286-2	340g/m2	440g/m2	0.5mm	0.6mm
	ASTM D-751.10	10oz/sq. yd	13oz/sq. yd	18oz/sq. yd	22oz/sq. yd
Yarn	Denier	1000x1000D	1000x1000D	NA	NA
Yarn Count	Per Inch	9x9	3x3	NA	NA
Tensile Strength Warp/Weft	DIN EN ISO 1421/V1	1300/1200	1100/1000	500/500	600/600
	ASTM D-751 B	N/50mm	N/50mm	N/50mm	N/50mm
Tear Strength Warp/Weft	DIN 53363	250/230	180/160	80/80	90/90
	ASTM D-751 (8 “ x 10 “) Specimen	N	N	N	N
Adhesion	ASTM D-751 RF Weld	N/50mm	N/50mm	N/50mm	N/50mm
Temperature resistance	DIN EN 1876-1 ASTM D-2136	(-40° C/+70° C, -40° C/+70° C, -40° C/+70° C, -40° C/+70° C, -40° C/+70° C.			
Fire behaviour	ISO 3795	B2	B2	B2	B2
Environmental Protective	EU				
Surface Treatment	Acrylic/PVDF				
Weather Protection		UV	UV	UV	UV
Special Property	Transparent				
Available Width	Meter	1-3.2m	1-3.2m	1-1.8m	1-1.8m

Leading China PVC Fabric Producer

www.chinatarps.com Manager@chinatarps.com 0086-13757342702